



Southern Illinois University System

Application

- Protective coating of aircraft brakes

Inventor

Don Jarlen, PhD

Dr. Jarlen is an emeritus professor of mechanical engineering and engineering processes at Southern Illinois University Carbondale.

Glass Ceramics-Based Antioxidants for the Oxidation Protection of Carbon-Carbon Composites

Carbon-carbon (C/C) composite brakes are one-third the weight of typical steel brakes and attain their strength and frictional properties at temperatures up to 1600° C. C/C brakes can endure high temperatures, but in the presence of oxygen they will begin to oxidize at 400° C such that anti-oxidant systems must be applied to the non-rubbing C/C composite surfaces. Currently, commercial coating materials made of crystalline metal phosphates that are derived from heat treating phosphoric acid-based liquid precursors and are painted on the surface of carbon-carbon composites. The coatings tend to be porous, discontinuous and sensitive to moisture causing decreased surface friction.

Invention

An SIU researcher has developed a series of methodologies to produce glass-ceramic coating materials for the oxidation protection of C-C composite brakes. The glass-ceramic coating systems are derived from uniquely formulated liquid precursors which, after heat treating, produce dense coatings comprising crystalline ceramic particles that are bonded by a continuous matrix phase of glass. Upon heating, the chemicals turn into an oxide mixture and form a glass-ceramic coating material that penetrates into the carbon-carbon composite to be protected. The base oxides of the glass-ceramic coating and their source raw materials covered in this invention are listed in Table 1.

TABLE 1

Base oxides and raw chemicals for the oxides used in the anti-oxidants.	
Base Oxides	Source Raw Materials
P ₂ O ₅	85% H ₃ PO ₄ , Al(H ₂ PO ₄) ₃ , KH ₂ PO ₄ , NaH ₂ PO ₄ , . . .
B ₂ O ₃	B ₂ O ₃ , K ₂ B ₄ O ₇ *10(H ₂ O), Na ₂ B ₄ O ₇ *4(H ₂ O), . . .
Al ₂ O ₃	Al(H ₂ PO ₄) ₃ , Al ₂ O ₃ , . . .
K ₂ O	K ₂ CO ₃ , KNO ₃ , KCl, KOH, KH ₂ PO ₄ , . . .
Na ₂ O	NaCO ₃ , NaNO ₃ , NaCl, NaOH, NaH ₂ PO ₄ ,
CaO	CaCO ₃ , CaCl ₂
MgO	MgCO ₃ , MgCl ₂

Key Advantages

- Coating bonds well to and protects C-C composite brakes
- Coating can be produced from a variety of raw materials

Status

U.S. patent #9,388,087 was issued on July 12, 2016. The technology is available for license.

Other opportunities related to this technology, included but not limited to sponsored and/or collaborative research, may be available. Please reach out to the designated contact identified at left for more information.

Contact

Kristy Owen

Assistant Director

kowen@siumed.edu

(217) 545-6397

913 N. Rutledge St. • P.O. Box 19631 • Springfield, Illinois 62794-9631

(217) 545-3824 • techtransfer@siumed.edu • <http://siusystem.edu/tech-transfer/>